

# IDV26

## DIRECT VENT GAS FIREPLACE INSERT



The Ultimate in Design, Engineering & Quality

The unit illustrated is an IDV26N Direct Vent Insert – Natural Gas, LOGF27 Log Set, I26CV1BL Clean View – Black, and IDV26RL Brick Liner.

# Convert your wood burning fireplace to gas, for a new standard of warmth, beauty, safety and convenience.



MODEL	IDV26N / IDV26NE	IDV26LP / IDV26LPE
FUEL	NATURAL	PROPANE
INPUT	30,000 BTU	30,000 BTU
LOW	21,000 BTU	25,000 BTU
FE (P.4.1-02)	65.3% / 67.2%	65.3% / 67.2%

#### MINIMUM FIREPLACE OPENING

	WIDTH	HEIGHT	DEPTH
IDV26	33"/28"*	19 1/2"	14 1/4"

\*Components In (CV1) 33", Components Out (CV2) 28"

#### CLEAN VIEW AND SURROUND SIZES

IDV26	WIDTH	HEIGHT
I26CV1	35 5/8"	22 3/4"
I26CV2	44 5/8"	26 5/8"
I26CV1DS (Designer Door)	35 5/8"	22 3/4"
I26CVPF1	35 5/8"	25 7/8"
I26CVPF2	44 7/8"	33 1/2"
I26S1	42"	27 1/2"
I26SU*	47 1/2"	35 5/8" / 28 5/8"***
I26SPF1	39 3/8"	29 3/4"

\* Universal Surround can be cut to size for custom application.

\*\*Dimension as a three sided surround

#### MINIMUM UNIT COVERAGE – CLEAN VIEW

IDV26	WIDTH	HEIGHT
I26CV1*	34 1/2"	22"
I26CV2*	41 1/2"	25 1/2"
I26CVPF1*	34 1/2"	25"
I26CVPF2*	41 1/2"	32 3/8"
I26CV1DS*	34 1/2"	22"

\*Back Frame Dimension of Clean View Kit

1. IDV26N Direct Vent Insert – Natural Gas, LOGF27 Log Set, I26CVPF2BL Clean View Picture Frame – Black, IDV26RL Refractory Brick Liner.
2. IDV26N Direct Vent Insert – Natural Gas, I26CV2PW Clean View Kit – Pewter, LOGF27 Log Set, IDV26RL Refractory Brick Liner.
3. IDV26N Direct Vent Insert – Natural Gas, LOGF27 Log Set – I26CV1DSBL Clean View – Designer Door – Black, I26S1BL Surround – Black, IDV26RL Refractory Brick Liner.
4. IDV26N Direct Vent Insert – Natural Gas, I26CV1CV Clean View Kit – Copper Vein, I26S1CV Surround – Copper Vein, LOGF27 Log Set, IDV26RL Refractory Brick Liner.

#### STANDARD FEATURES\*

- Dual Burner with glowing embers
- Millivolt or IPI valve system allows operation during power failure with Hi-Low heat and flame control
- Matchless Piezo Ignition
- Decorative Ash Bed
- Ceramic Glass (Heat Radiating)
- On/Off Rocker switch
- Heat activated blower with variable speed control
- Bedroom and bed sitting room approval

#### OPTIONAL FEATURES\*

- Log Set – Fibre Split Oak
- Glass Tray with Bronze Glass
- Clean View Kit – Black, Pewter, Copper Vein
- Clean View Picture Frame – Black, Pewter, Copper Vein
- Surrounds for Clean View – Black, Copper Vein and Pewter
- Surround Picture Frame for Clean View – Black, Pewter, Copper Vein
- Porcelain Reflective Liners
- Brick Liner – Traditional
- Wall Mount Thermostat – Standard On/Off or Programmable
- Remote Control – On/Off, Thermostat, or Modulating Hi/Lo with Thermostat
- Designer Doors – Straight Door



The Ultimate in Design, Engineering & Quality

The unit illustrated is an IDV26N Vent Insert – Natural Gas, I26CVPF1BL Clean View Picture Frame – Black, LOGF27 Log Set, IDV26RL Refractory Brick Liner.

Kingsman Fireplaces, maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.  
Certification: Certified for Canada/USA as a Vented Gas Fireplace Heater  
ANSI Z21.88-2009, CSA 2.33-2009, CGA 2.17-M91.

\*Components may have to be ordered separately to create a complete unit.  
Discuss with your local Kingsman dealer for clarification.



Printed in Canada 04/13 B076



2340 Logan Avenue  
Winnipeg, Manitoba, Canada R2R 2V3  
Phone: (204) 632-1962 Fax: (204) 632-1960  
www.kingsmanfireplaces.com

# IDV26

DIRECT VENT GAS FIREPLACE INSERT



The Ultimate in Design, Engineering & Quality